

CSA 細芯控制電纜

- 適用領域及範圍：室內主支幹線配電、配電盤內用線或移動設備電源之相關控制線路。
- 額定電壓：600V
- 額定溫度：60°C
- 導體：裸軟銅線 B.C
- 絕緣 / 被覆：PVC 聚氯乙烯
- 規範：通過 CSA 標準。
- 特性：具良好之柔軟度，方便施工。



產品類別	產品編號	截面積 × 芯數 mm ² × C	導體		絕緣		被覆厚度 mm	完成外徑 mm	最大導體電阻 Ω/km	最小絕緣電阻 MΩ-km
			構造 NO./mm	外徑 mm	厚度 mm	外徑 mm				
CSA 細芯 控制電纜 (0.3 mm ²)	IF03502	0.3 mm ² × 2C	12/0.18	0.72	0.39	1.50	0.6	4.5	61.9	50
	IF03503	0.3 mm ² × 3C	12/0.18	0.72	0.39	1.50	0.6	4.8	61.9	50
	IF03504	0.3 mm ² × 4C	12/0.18	0.72	0.39	1.50	0.6	5.0	61.9	50
	IF03505	0.3 mm ² × 5C	12/0.18	0.72	0.39	1.50	0.6	5.8	61.9	50
	IF03506	0.3 mm ² × 6C	12/0.18	0.72	0.39	1.50	0.6	6.5	61.9	50
	IF03507	0.3 mm ² × 7C	12/0.18	0.72	0.39	1.50	0.6	6.5	61.9	50
	IF03508	0.3 mm ² × 8C	12/0.18	0.72	0.39	1.50	0.7	7.0	61.9	50
	IF03510	0.3 mm ² × 10C	12/0.18	0.72	0.39	1.50	0.8	8.0	61.9	50
	IF03512	0.3 mm ² × 12C	12/0.18	0.72	0.39	1.50	0.8	8.5	61.9	50
	IF03516	0.3 mm ² × 16C	12/0.18	0.72	0.39	1.50	0.9	9.5	61.9	50
	IF03520	0.3 mm ² × 20C	12/0.18	0.72	0.39	1.50	1.0	10.5	61.9	50
	IF03524	0.3 mm ² × 24C	12/0.18	0.72	0.39	1.50	1.0	11.8	61.9	50
	IF03530	0.3 mm ² × 30C	12/0.18	0.72	0.39	1.50	1.0	12.5	61.9	50
	IF03536	0.3 mm ² × 36C	12/0.18	0.72	0.39	1.50	1.0	13.5	61.9	50
	IF03540	0.3 mm ² × 40C	12/0.18	0.72	0.39	1.50	1.1	14.5	61.9	50
	IF03550	0.3 mm ² × 50C	12/0.18	0.72	0.39	1.50	1.1	15.5	61.9	50
	CSA 細芯 控制電纜 (0.5 mm ²)	IF05002	0.5 mm ² × 2C	20/0.18	0.95	0.43	1.80	0.8	5.0	36.7
IF05003		0.5 mm ² × 3C	20/0.18	0.95	0.43	1.80	0.8	5.3	36.7	50
IF05004		0.5 mm ² × 4C	20/0.18	0.95	0.43	1.80	0.8	6.0	36.7	50
IF05005		0.5 mm ² × 5C	20/0.18	0.95	0.43	1.80	0.8	6.8	36.7	50
IF05006		0.5 mm ² × 6C	20/0.18	0.95	0.43	1.80	0.8	7.5	36.7	50
IF05007		0.5 mm ² × 7C	20/0.18	0.95	0.43	1.80	0.8	7.5	36.7	50
IF05008		0.5 mm ² × 8C	20/0.18	0.95	0.43	1.80	1.0	8.0	36.7	50
IF05010		0.5 mm ² × 10C	20/0.18	0.95	0.43	1.80	1.0	9.5	36.7	50
IF05012		0.5 mm ² × 12C	20/0.18	0.95	0.43	1.80	1.0	10.0	36.7	50
IF05016		0.5 mm ² × 16C	20/0.18	0.95	0.43	1.80	1.1	11.0	36.7	50
IF05020		0.5 mm ² × 20C	20/0.18	0.95	0.43	1.80	1.3	12.5	36.7	50
IF05024		0.5 mm ² × 24C	20/0.18	0.95	0.43	1.80	1.3	13.3	36.7	50
IF05030		0.5 mm ² × 30C	20/0.18	0.95	0.43	1.80	1.4	15.0	36.7	50
IF05036		0.5 mm ² × 36C	20/0.18	0.95	0.43	1.80	1.4	15.8	36.7	50
IF05040		0.5 mm ² × 40C	20/0.18	0.95	0.43	1.80	1.5	16.2	36.7	50
IF05050		0.5 mm ² × 50C	20/0.18	0.95	0.43	1.80	1.5	18.2	36.7	50
CSA 細芯 控制電纜 (0.75 mm ²)		IF07502	0.75 mm ² × 2C	30/0.18	1.15	0.58	2.30	1.0	6.5	24.4
	IF07503	0.75 mm ² × 3C	30/0.18	1.15	0.58	2.30	1.0	7.0	24.4	50
	IF07504	0.75 mm ² × 4C	30/0.18	1.15	0.58	2.30	1.0	7.5	24.4	50
	IF07505	0.75 mm ² × 5C	30/0.18	1.15	0.58	2.30	1.0	8.5	24.4	50
	IF07506	0.75 mm ² × 6C	30/0.18	1.15	0.58	2.30	1.1	9.5	24.4	50
	IF07507	0.75 mm ² × 7C	30/0.18	1.15	0.58	2.30	1.1	9.5	24.4	50
	IF07508	0.75 mm ² × 8C	30/0.18	1.15	0.58	2.30	1.2	10.1	24.4	50
	IF07510	0.75 mm ² × 10C	30/0.18	1.15	0.58	2.30	1.2	11.0	24.4	50
	IF07512	0.75 mm ² × 12C	30/0.18	1.15	0.58	2.30	1.2	11.8	24.4	50
	IF07516	0.75 mm ² × 16C	30/0.18	1.15	0.58	2.30	1.4	13.5	24.4	50

產品類別	產品編號	截面積 × 芯數 mm ² × C	導體		絕緣		被覆厚度 mm	完成外徑 mm	最大導體電阻 Ω/km	最小絕緣電阻 MΩ-km
			構造 NO./mm	外徑 mm	厚度 mm	外徑 mm				
CSA 細芯 控制電纜 (0.75 mm ²)	IF07520	0.75 mm ² × 20C	30/0.18	1.15	0.58	2.30	1.4	15.3	24.4	50
	IF07524	0.75 mm ² × 24C	30/0.18	1.15	0.58	2.30	1.5	16.9	24.4	50
	IF07530	0.75 mm ² × 30C	30/0.18	1.15	0.58	2.30	1.5	17.8	24.4	50
	IF07536	0.75 mm ² × 36C	30/0.18	1.15	0.58	2.30	1.5	19.4	24.4	50
	IF07540	0.75 mm ² × 40C	30/0.18	1.15	0.58	2.30	1.6	20.1	24.4	50
	IF07550	0.75 mm ² × 50C	30/0.18	1.15	0.58	2.30	1.8	23.5	24.4	50
CSA 細芯 控制電纜 (1.25 mm ²)	IF12502	1.25 mm ² × 2C	50/0.18	1.50	0.51	2.50	1.0	6.8	15.1	50
	IF12503	1.25 mm ² × 3C	50/0.18	1.50	0.51	2.50	1.1	7.5	15.1	50
	IF12504	1.25 mm ² × 4C	50/0.18	1.50	0.51	2.50	1.2	7.8	15.1	50
	IF12505	1.25 mm ² × 5C	50/0.18	1.50	0.51	2.50	1.2	8.8	15.1	50
	IF12506	1.25 mm ² × 6C	50/0.18	1.50	0.51	2.50	1.3	10.0	15.1	50
	IF12507	1.25 mm ² × 7C	50/0.18	1.50	0.51	2.50	1.3	10.0	15.1	50
	IF12508	1.25 mm ² × 8C	50/0.18	1.50	0.51	2.50	1.3	11.0	15.1	50
	IF12510	1.25 mm ² × 10C	50/0.18	1.50	0.51	2.50	1.3	13.0	15.1	50
	IF12512	1.25 mm ² × 12C	50/0.18	1.50	0.51	2.50	1.3	13.2	15.1	50
	IF12516	1.25 mm ² × 16C	50/0.18	1.50	0.51	2.50	1.3	14.8	15.1	50
	IF12520	1.25 mm ² × 20C	50/0.18	1.50	0.51	2.50	1.3	16.3	15.1	50
	IF12524	1.25 mm ² × 24C	50/0.18	1.50	0.51	2.50	1.5	18.0	15.1	50
	IF12530	1.25 mm ² × 30C	50/0.18	1.50	0.51	2.50	1.5	19.0	15.1	50
	IF12536	1.25 mm ² × 36C	50/0.18	1.50	0.51	2.50	1.6	20.8	15.1	50
	IF12540	1.25 mm ² × 40C	50/0.18	1.50	0.51	2.50	1.6	21.9	15.1	50
	IF12550	1.25 mm ² × 50C	50/0.18	1.50	0.51	2.50	1.8	24.5	15.1	50
	CSA 細芯 控制電纜 (2 mm ²)	IF20002	2 mm ² × 2C	37/0.26	1.80	0.60	3.00	1.2	8.0	9.79
IF20003		2 mm ² × 3C	37/0.26	1.80	0.60	3.00	1.3	8.5	9.79	50
IF20004		2 mm ² × 4C	37/0.26	1.80	0.60	3.00	1.3	9.5	9.79	50
IF20005		2 mm ² × 5C	37/0.26	1.80	0.60	3.00	1.3	10.6	9.79	50
IF20006		2 mm ² × 6C	37/0.26	1.80	0.60	3.00	1.4	12.0	9.79	50
IF20007		2 mm ² × 7C	37/0.26	1.80	0.60	3.00	1.5	12.0	9.79	50
IF20008		2 mm ² × 8C	37/0.26	1.80	0.60	3.00	1.5	13.0	9.79	50
IF20010		2 mm ² × 10C	37/0.26	1.80	0.60	3.00	1.5	15.1	9.79	50
IF20012		2 mm ² × 12C	37/0.26	1.80	0.60	3.00	1.5	15.5	9.79	50
IF20016		2 mm ² × 16C	37/0.26	1.80	0.60	3.00	1.5	17.1	9.79	50
IF20020		2 mm ² × 20C	37/0.26	1.80	0.60	3.00	1.6	18.6	9.79	50
IF20024		2 mm ² × 24C	37/0.26	1.80	0.60	3.00	1.8	21.4	9.79	50
IF20030		2 mm ² × 30C	37/0.26	1.80	0.60	3.00	1.8	23.0	9.79	50
IF20036		2 mm ² × 36C	37/0.26	1.80	0.60	3.00	1.9	24.8	9.79	50
CSA 細芯 控制電纜 (3.5 mm ²)	IF35002	3.5 mm ² × 2C	65/0.26	2.40	0.82	4.00	1.2	10.5	5.42	50
	IF35003	3.5 mm ² × 3C	65/0.26	2.40	0.82	4.00	1.2	10.8	5.42	50
	IF35004	3.5 mm ² × 4C	65/0.26	2.40	0.82	4.00	1.4	12.5	5.42	50
	IF35005	3.5 mm ² × 5C	65/0.26	2.40	0.82	4.00	1.5	14.0	5.42	50
	IF35006	3.5 mm ² × 6C	65/0.26	2.40	0.82	4.00	1.5	15.0	5.42	50
	IF35007	3.5 mm ² × 7C	65/0.26	2.40	0.82	4.00	1.5	15.0	5.42	50
	CSA 細芯 控制電纜 (5.5 mm ²)	IF55002	5.5 mm ² × 2C	104/0.26	3.00	1.00	5.00	1.5	12.0	6.10
IF55003		5.5 mm ² × 3C	104/0.26	3.00	1.00	5.00	1.5	14.2	6.10	50
IF55004		5.5 mm ² × 4C	104/0.26	3.00	1.00	5.00	1.5	15.6	6.10	50
IF55005		5.5 mm ² × 5C	104/0.26	3.00	1.00	5.00	1.5	16.5	6.10	50
IF55006		5.5 mm ² × 6C	104/0.26	3.00	1.00	5.00	1.6	18.2	6.10	50
IF55007		5.5 mm ² × 7C	104/0.26	3.00	1.00	5.00	1.6	18.2	6.10	50
CSA 細芯 控制電纜 (8 mm ²)		IF80002	8 mm ² × 2C	148/0.26	3.70	1.20	6.00	1.4	14.0	2.54
	IF80003	8 mm ² × 3C	148/0.26	3.70	1.20	6.00	1.5	16.5	2.54	50
	IF80004	8 mm ² × 4C	148/0.26	3.70	1.20	6.00	1.5	18.0	2.54	50
CSA 細芯 控制電纜 (14 mm ²)	IF140002	14 mm ² × 2C	259/0.26	4.90	1.20	7.30	1.7	17.5	1.43	30
	IF140003	14 mm ² × 3C	259/0.26	4.90	1.20	7.30	1.8	20.0	1.43	30
	IF140004	14 mm ² × 4C	259/0.26	4.90	1.20	7.30	1.8	22.0	1.43	30
CSA 細芯 控制電纜 (22 mm ²)	IF220004	22 mm ² × 4C	420/0.26	6.80	1.30	9.50	1.8	27.0	0.89	30