

CSA 細芯鋁箔銅網 雙隔離電纜 ★另可訂製 CSA 單隔離電纜 (鋁箔 A+ 地線 E) 產品, 歡迎洽詢

- 適用領域及範圍：自動迴路控制、儀器設備之訊號控制、中央監控類比訊號傳輸。
- 額定電壓：600V
- 額定溫度：60°C
- 導體：裸軟銅線 B.C
- 絕緣：PVC 聚氯乙烯
- 遮蔽：鋁箔 A+ 銅網 B
- 被覆：PVC 聚氯乙烯
- 規範：通過 CSA 標準。
- 特性：具良好之柔軟度方便施工，遮蔽層可防止訊號遭受干擾。



產品類別	產品編號	截面積 × 芯數 mm ² × C	導體		絕緣		被覆厚度 mm	完成外徑 mm	最大導體電阻 Ω/km	最小絕緣電阻 MΩ-km
			構造 NO./mm	外徑 mm	厚度 mm	外徑 mm				
CSA 細芯 鋁箔銅網 雙隔離電纜 (0.5 mm ²)	IB05002	0.5 mm ² × 2C	20/0.18	0.95	0.43	1.80	0.90	5.6	36.7	50
	IB05003	0.5 mm ² × 3C	20/0.18	0.95	0.43	1.80	0.90	6.0	36.7	50
	IB05004	0.5 mm ² × 4C	20/0.18	0.95	0.43	1.80	0.90	7.0	36.7	50
	IB05005	0.5 mm ² × 5C	20/0.18	0.95	0.43	1.80	1.00	7.5	36.7	50
	IB05006	0.5 mm ² × 6C	20/0.18	0.95	0.43	1.80	1.00	8.0	36.7	50
	IB05007	0.5 mm ² × 7C	20/0.18	0.95	0.43	1.80	1.00	8.0	36.7	50
	IB05008	0.5 mm ² × 8C	20/0.18	0.95	0.43	1.80	1.00	8.5	36.7	50
	IB05010	0.5 mm ² × 10C	20/0.18	0.95	0.43	1.80	1.00	9.5	36.7	50
	IB05012	0.5 mm ² × 12C	20/0.18	0.95	0.43	1.80	1.00	10.0	36.7	50
	IB05016	0.5 mm ² × 16C	20/0.18	0.95	0.43	1.80	1.30	11.5	36.7	50
	IB05020	0.5 mm ² × 20C	20/0.18	0.95	0.43	1.80	1.30	13.2	36.7	50
	IB05024	0.5 mm ² × 24C	20/0.18	0.95	0.43	1.80	1.30	14.5	36.7	50
	IB05030	0.5 mm ² × 30C	20/0.18	0.95	0.43	1.80	1.40	15.6	36.7	50
	IB05036	0.5 mm ² × 36C	20/0.18	0.95	0.43	1.80	1.40	16.5	36.7	50
	IB05040	0.5 mm ² × 40C	20/0.18	0.95	0.43	1.80	1.50	17.0	36.7	50
CSA 細芯 鋁箔銅網 雙隔離電纜 (0.75 mm ²)	IB07502	0.75 mm ² × 2C	30/0.18	1.15	0.58	2.30	1.00	7.0	24.4	50
	IB07503	0.75 mm ² × 3C	30/0.18	1.15	0.58	2.30	1.00	7.5	24.4	50
	IB07504	0.75 mm ² × 4C	30/0.18	1.15	0.58	2.30	1.00	8.5	24.4	50
	IB07505	0.75 mm ² × 5C	30/0.18	1.15	0.58	2.30	1.00	9.0	24.4	50
	IB07506	0.75 mm ² × 6C	30/0.18	1.15	0.58	2.30	1.00	10.0	24.4	50
	IB07507	0.75 mm ² × 7C	30/0.18	1.15	0.58	2.30	1.20	10.0	24.4	50
	IB07508	0.75 mm ² × 8C	30/0.18	1.15	0.58	2.30	1.20	10.5	24.4	50
	IB07510	0.75 mm ² × 10C	30/0.18	1.15	0.58	2.30	1.20	11.5	24.4	50
	IB07512	0.75 mm ² × 12C	30/0.18	1.15	0.58	2.30	1.20	12.5	24.4	50
	IB07516	0.75 mm ² × 16C	30/0.18	1.15	0.58	2.30	1.40	14.0	24.4	50
	IB07520	0.75 mm ² × 20C	30/0.18	1.15	0.58	2.30	1.40	16.0	24.4	50
	IB07524	0.75 mm ² × 24C	30/0.18	1.15	0.58	2.30	1.50	17.5	24.4	50
	IB07530	0.75 mm ² × 30C	30/0.18	1.15	0.58	2.30	1.50	18.5	24.4	50
	IB07536	0.75 mm ² × 36C	30/0.18	1.15	0.58	2.30	1.60	20.0	24.4	50
	IB07540	0.75 mm ² × 40C	30/0.18	1.15	0.58	2.30	1.60	21.2	24.4	50
IB07550	0.75 mm ² × 50C	30/0.18	1.15	0.58	2.30	1.70	24.0	24.4	50	

產品類別	產品編號	截面積 × 芯數 mm ² × C	導體		絕緣		被覆厚度 mm	完成外徑 mm	最大導體電阻 Ω/km	最小絕緣電阻 MΩ-km
			構造 NO./mm	外徑 mm	厚度 mm	外徑 mm				
CSA 細芯 鋁箔銅網 雙隔離電纜 (1.25 mm ²)	IB12502	1.25 mm ² × 2C	50/0.18	1.50	0.51	2.50	1.00	7.5	15.1	50
	IB12503	1.25 mm ² × 3C	50/0.18	1.50	0.51	2.50	1.10	8.0	15.1	50
	IB12504	1.25 mm ² × 4C	50/0.18	1.50	0.51	2.50	1.10	9.0	15.1	50
	IB12505	1.25 mm ² × 5C	50/0.18	1.50	0.51	2.50	1.10	9.5	15.1	50
	IB12506	1.25 mm ² × 6C	50/0.18	1.50	0.51	2.50	1.10	10.5	15.1	50
	IB12507	1.25 mm ² × 7C	50/0.18	1.50	0.51	2.50	1.10	10.5	15.1	50
	IB12508	1.25 mm ² × 8C	50/0.18	1.50	0.51	2.50	1.20	11.5	15.1	50
	IB12510	1.25 mm ² × 10C	50/0.18	1.50	0.51	2.50	1.20	13.0	15.1	50
	IB12512	1.25 mm ² × 12C	50/0.18	1.50	0.51	2.50	1.20	13.6	15.1	50
	IB12516	1.25 mm ² × 16C	50/0.18	1.50	0.51	2.50	1.20	16.0	15.1	50
	IB12520	1.25 mm ² × 20C	50/0.18	1.50	0.51	2.50	1.30	17.0	15.1	50
	IB12524	1.25 mm ² × 24C	50/0.18	1.50	0.51	2.50	1.50	19.0	15.1	50
	IB12530	1.25 mm ² × 30C	50/0.18	1.50	0.51	2.50	1.50	20.8	15.1	50
	IB12536	1.25 mm ² × 36C	50/0.18	1.50	0.51	2.50	1.60	22.0	15.1	50
	IB12540	1.25 mm ² × 40C	50/0.18	1.50	0.51	2.50	1.60	23.0	15.1	50
IB12550	1.25 mm ² × 50C	50/0.18	1.50	0.51	2.50	1.80	25.0	15.1	50	
CSA 細芯 鋁箔銅網 雙隔離電纜 (2 mm ²)	IB20002	2 mm ² × 2C	37/0.26	1.80	0.60	3.00	1.10	8.5	9.79	50
	IB20003	2 mm ² × 3C	37/0.26	1.80	0.60	3.00	1.10	9.0	9.79	50
	IB20004	2 mm ² × 4C	37/0.26	1.80	0.60	3.00	1.20	10.0	9.79	50
	IB20005	2 mm ² × 5C	37/0.26	1.80	0.60	3.00	1.20	10.8	9.79	50
	IB20006	2 mm ² × 6C	37/0.26	1.80	0.60	3.00	1.30	12.0	9.79	50
	IB20007	2 mm ² × 7C	37/0.26	1.80	0.60	3.00	1.30	12.0	9.79	50
	IB20008	2 mm ² × 8C	37/0.26	1.80	0.60	3.00	1.30	13.0	9.79	50
	IB20010	2 mm ² × 10C	37/0.26	1.80	0.60	3.00	1.40	15.0	9.79	50
	IB20012	2 mm ² × 12C	37/0.26	1.80	0.60	3.00	1.40	15.8	9.79	50
	IB20016	2 mm ² × 16C	37/0.26	1.80	0.60	3.00	1.50	17.0	9.79	50
	IB20020	2 mm ² × 20C	37/0.26	1.80	0.60	3.00	1.50	19.5	9.79	50
	IB20024	2 mm ² × 24C	37/0.26	1.80	0.60	3.00	1.60	21.8	9.79	50
IB20030	2 mm ² × 30C	37/0.26	1.80	0.60	3.00	1.80	23.5	9.79	50	
IB20036	2 mm ² × 36C	37/0.26	1.80	0.60	3.00	1.90	25.5	9.79	50	