

• CNS3301 600V PVC-PVC 電力電纜

★ 50mm<sup>2</sup> 以上產品非常備規格品需另確認庫存或以 MOQ 訂製

- 適用領域及範圍：一般電路支配線。
- 額定電壓：600V
- 額定溫度：60°C
- 導體：圓形或圓形壓縮銅絞線。
- 絕緣 / 被覆：PVC 聚氯乙烯
- 規範：通過 CNS3301 標準。
- 芯色：1) 黑、2) 白、3) 紅、4) 綠



產品類別	產品編號	截面積 × 芯數 mm <sup>2</sup> × C	導體		絕緣厚度 mm	被覆厚度 mm	完成外徑 mm	最大導體電阻 Ω/km	最小絕緣電阻 MΩ-km	重量 (約) Kg/km
			構造 NO./mm	外徑 mm						
CNS3301 600V PVC-PVC 電力電纜 (2C)	WV0012502	1.25 mm <sup>2</sup> × 2C	7/0.45	1.35	0.8	1.5	9.0	16.8	50	100
	WV0020002	2 mm <sup>2</sup> × 2C	7/0.6	1.8	0.8	1.5	10.5	9.42	50	135
	WV0035002	3.5 mm <sup>2</sup> × 2C	7/0.8	2.4	0.8	1.5	11.5	5.30	50	180
	WV0055002	5.5 mm <sup>2</sup> × 2C	7/1.0	3.0	1.0	1.5	13.5	3.40	50	260
	WV0080002	8 mm <sup>2</sup> × 2C	7/1.2	3.6	1.2	1.5	15.5	2.36	50	360
	WV0140002	14 mm <sup>2</sup> × 2C	7/1.6	4.8	1.4	1.5	19.0	1.33	40	555
	WV0220002	22 mm <sup>2</sup> × 2C	7/2.0	6.0	1.6	1.6	22	0.840	40	815
	WV0300002	30 mm <sup>2</sup> × 2C	7/2.3	6.9	1.6	1.6	24	0.635	40	935
	WV0380002	38 mm <sup>2</sup> × 2C	7/2.6	7.8	1.8	1.7	27	0.497	40	1250
	WV0500002	50 mm <sup>2</sup> × 2C	圓形 壓縮	8.4	1.8	1.8	28	0.373	30	1520
	WV0600002	60 mm <sup>2</sup> × 2C		9.3	1.8	1.9	31	0.311	30	1820
	WV0800002	80 mm <sup>2</sup> × 2C		10.7	2.0	2.0	34	0.234	30	2360
	WV1000002	100 mm <sup>2</sup> × 2C		12.0	2.0	2.1	37	0.187	30	2900
	WV1250002	125 mm <sup>2</sup> × 2C		13.5	2.2	2.2	41	0.149	30	3550
	WV1500002	150 mm <sup>2</sup> × 2C		14.7	2.2	2.3	44	0.124	30	4100
	WV2000002	200 mm <sup>2</sup> × 2C		17.0	2.4	2.6	50	0.0933	20	5170
WV2500002	250 mm <sup>2</sup> × 2C	19.0		2.4	2.7	54	0.0754	20	6530	
WV3250002	325 mm <sup>2</sup> × 2C	21.7	2.6	3.0	61	0.0579	20	8230		
CNS3301 600V PVC-PVC 電力電纜 (3C)	WV0012503	1.25 mm <sup>2</sup> × 3C	7/0.45	1.35	0.8	1.5	9.5	16.8	50	120
	WV0020003	2 mm <sup>2</sup> × 3C	7/0.6	1.8	0.8	1.5	11.0	9.42	50	165
	WV0035003	3.5 mm <sup>2</sup> × 3C	7/0.8	2.4	0.8	1.5	12.5	5.30	50	235
	WV0055003	5.5 mm <sup>2</sup> × 3C	7/1.0	3.0	1.0	1.5	14.5	3.40	50	335
	WV0080003	8 mm <sup>2</sup> × 3C	7/1.2	3.6	1.2	1.5	16.5	2.36	50	465
	WV0140003	14 mm <sup>2</sup> × 3C	7/1.6	4.8	1.4	1.5	20	1.33	40	740
	WV0220003	22 mm <sup>2</sup> × 3C	7/2.0	6.0	1.6	1.6	24	0.840	40	1070
	WV0300003	30 mm <sup>2</sup> × 3C	7/2.3	6.9	1.6	1.7	26	0.635	40	1340
	WV0380003	38 mm <sup>2</sup> × 3C	7/2.6	7.8	1.8	1.8	29	0.497	40	1690

產品類別	產品編號	截面積 × 芯數 mm <sup>2</sup> × C	導體		絕緣 厚度 mm	被覆厚度 mm	完成外徑 mm	最大導體電阻 Ω/km	最小絕緣電阻 MΩ-km	重量 (約) Kg/km
			構造 NO./mm	外徑 mm						
CNS3301 600V PVC-PVC 電力電纜 (3C)	WV050003	50 mm <sup>2</sup> × 3C	圓形 壓縮	8.4	1.8	1.8	30	0.373	30	2090
	WV060003	60 mm <sup>2</sup> × 3C		9.3	1.8	1.9	33	0.311	30	2480
	WV080003	80 mm <sup>2</sup> × 3C		10.7	2.0	2.1	37	0.234	30	3250
	WV100003	100 mm <sup>2</sup> × 3C		12.0	2.0	2.2	40	0.187	30	3990
	WV125003	125 mm <sup>2</sup> × 3C		13.5	2.2	2.3	44	0.149	30	4910
	WV150003	150 mm <sup>2</sup> × 3C		14.7	2.2	2.5	47	0.124	30	5810
	WV200003	200 mm <sup>2</sup> × 3C		17.0	2.4	2.7	53	0.0933	20	7330
	WV250003	250 mm <sup>2</sup> × 3C		19.0	2.4	2.9	58	0.0754	20	9300
WV325003	325 mm <sup>2</sup> × 3C	21.7	2.6	3.1	65	0.0579	20	11780		
CNS3301 600V PVC-PVC 電力電纜 (4C)	WV0012504	1.25 mm <sup>2</sup> × 4C	7/0.45	1.35	0.8	1.5	10.5	16.8	50	150
	WV0020004	2 mm <sup>2</sup> × 4C	7/0.6	1.8	0.8	1.5	12.0	9.42	50	200
	WV0035004	3.5 mm <sup>2</sup> × 4C	7/0.8	2.4	0.8	1.5	13.5	5.30	50	290
	WV0055004	5.5 mm <sup>2</sup> × 4C	7/1.0	3.0	1.0	1.5	16.0	3.40	50	420
	WV0080004	8 mm <sup>2</sup> × 4C	7/1.2	3.6	1.2	1.5	18.0	2.36	50	590
	WV0140004	14 mm <sup>2</sup> × 4C	7/1.6	4.8	1.4	1.6	22	1.33	40	945
	WV0220004	22 mm <sup>2</sup> × 4C	7/2.0	6.0	1.6	1.7	27	0.840	40	1390
	WV0300004	30 mm <sup>2</sup> × 4C	7/2.3	6.9	1.6	1.8	28	0.635	40	1720
	WV0380004	38 mm <sup>2</sup> × 4C	7/2.6	7.8	1.8	1.9	32	0.497	40	2180
	WV0500004	50 mm <sup>2</sup> × 4C	圓形 壓縮	8.4	1.8	2.0	34	0.373	30	2690
	WV0600004	60 mm <sup>2</sup> × 4C		9.3	1.8	2.1	36	0.311	30	3210
	WV0800004	80 mm <sup>2</sup> × 4C		10.7	2.0	2.2	41	0.234	30	4200
	WV1000004	100 mm <sup>2</sup> × 4C		12.0	2.0	2.4	44	0.187	30	5200
	WV1250004	125 mm <sup>2</sup> × 4C		13.5	2.2	2.5	49	0.149	30	6380
	WV1500004	150 mm <sup>2</sup> × 4C		14.7	2.2	2.7	52	0.124	30	7550
	WV2000004	200 mm <sup>2</sup> × 4C		17.0	2.4	2.9	59	0.0933	20	9600
WV2500004	250 mm <sup>2</sup> × 4C	19.0		2.4	3.1	65	0.0754	20	12200	
WV3250004	325 mm <sup>2</sup> × 4C	21.7	2.6	3.4	73	0.0579	20	15500		