

• CNS2655 XLPE-PVC 交連 PE 電力電纜

★ 50 mm² 以上產品非常被規格品需另確認庫存或以 MOQ 訂製

- 適用領域及範圍：輸配電系統
- 額定電壓：600V~25KV
- 額定溫度：90°C
- 導體：圓形或圓形壓縮銅絞線
- 絕緣：XLPE 交連 PE
- 被覆：PVC 聚氯乙烯
- 規範：通過 CNS2655 標準
- 芯色：1) 黑、2) 白、3) 紅、4) 綠



產品類別	產品編號	截面積 × 芯數 mm ² × C	導體		絕緣 厚度 mm	被覆厚度 mm	完成外徑 mm	最大導 體電阻 Ω/km	最小絕 緣電阻 MΩ-km	重量 (約)Kg/km	
			構造 NO./mm	外徑 mm							
CNS2655 600V XLPE 電力電纜 (1C)	CV002001	2mm ² × 1C	7/0.6	1.8	0.76	0.38	4.4	9.24	2500	35	
	CV003501	3.5mm ² × 1C	7/0.8	2.4	0.76	0.38	5.0	5.20	2000	51	
	CV005501	5.5mm ² × 1C	7/1.0	3.0	0.76	0.38	5.6	3.33	2000	72	
	CV008001	8mm ² × 1C	7/1.2	3.6	1.14	0.38	6.6	2.31	1500	106	
	CV014001	14mm ² × 1C	圓形 壓縮	4.4	1.14	0.76	8.7	1.30	1500	177	
	CV022001	22mm ² × 1C		5.5	1.14	0.76	9.8	0.824	1500	258	
	CV030001	30mm ² × 1C		6.3	1.40	0.76	11.1	0.623	1500	331	
	CV038001	38mm ² × 1C		7.1	1.40	0.76	11.9	0.487	1000	420	
	CV050001	50mm ² × 1C		8.2	1.40	1.14	13.7	0.378	1000	552	
	CV060001	60mm ² × 1C		9.1	1.40	1.14	14.6	0.303	1000	665	
	CV080001	80mm ² × 1C		10.5	1.40	1.14	16.0	0.229	1000	853	
	CV100001	100mm ² × 1C		11.9	1.40	1.14	17.4	0.180	800	1067	
	CV125001	125mm ² × 1C		13.2	1.65	1.14	19.2	0.144	800	1367	
	CV150001	150mm ² × 1C		14.7	1.65	1.65	21.7	0.118	800	1612	
	CV200001	200mm ² × 1C		16.6	1.65	1.65	23.6	0.0922	800	2021	
	CV250001	250mm ² × 1C		18.9	1.65	1.65	25.9	0.0722	600	2506	
CV325001	325mm ² × 1C	21.3		2.03	1.65	29.1	0.0565	600	3234		
CNS2655 600V XLPE 電力電纜 (2C)	CV002002	2mm ² × 2C		7/0.6	1.8	0.76	1.14	9.8	9.42	2500	143
	CV003502	3.5mm ² × 2C		7/0.8	2.4	0.76	1.14	11.0	5.30	2000	197
	CV005502	5.5mm ² × 2C		7/1.0	3.0	0.76	1.14	12.2	3.40	2000	257
	CV008002	8mm ² × 2C	7/1.2	3.6	1.14	1.52	16.0	2.36	1500	296	
	CV014002	14mm ² × 2C	7/1.6	4.4	1.14	1.52	17.2	1.33	1500	557	
	CV022002	22mm ² × 2C	7/2.0	5.5	1.14	1.52	19.5	0.840	1500	771	
	CV030002	30mm ² × 2C	7/2.3	6.3	1.40	2.03	23.1	0.635	1500	1014	
	CV038002	38mm ² × 2C	7/2.6	7.1	1.40	2.03	24.7	0.497	1000	1274	
	CV050002	50mm ² × 2C	圓形 壓縮	8.2	1.40	2.03	26.9	0.386	1000	1356	
	CV060002	60mm ² × 2C		9.1	1.40	2.03	28.7	0.309	1000	1617	
	CV080002	80mm ² × 2C		10.5	1.40	2.03	31.5	0.234	1000	2052	
	CV100002	100mm ² × 2C		11.9	1.40	2.03	34.3	0.184	800	2401	
	CV125002	125mm ² × 2C		13.2	1.65	2.03	37.9	0.147	800	2985	
	CV150002	150mm ² × 2C		14.7	1.65	2.03	40.9	0.120	800	4011	
	CV200002	200mm ² × 2C		16.6	1.65	2.79	46.4	0.0940	800	5021	
	CV250002	250mm ² × 2C		18.9	1.65	2.79	51.0	0.0736	600	6202	
CV325002	325mm ² × 2C	21.3		2.03	2.79	57.4	0.0576	600	7702		

產品類別	產品編號	截面積 × 芯數 mm ² × C	導體		絕緣 厚度 mm	被覆厚度 mm	完成外徑 mm	最大導 體電阻 Ω/km	最小絕 緣電阻 MΩ-km	重量 (約)Kg/km	
			構造 NO./mm	外徑 mm							
CNS2655 600V XLPE 電力電纜 (3C)	CV002003	2mm ² × 3C	7/0.6	1.8	0.76	1.14	10.4	9.42	2500	168	
	CV003503	3.5mm ² × 3C	7/0.8	2.4	0.76	1.14	11.6	5.30	2000	235	
	CV005503	5.5mm ² × 3C	7/1.0	3.0	0.76	1.14	12.9	3.40	2000	315	
	CV008003	8mm ² × 3C	7/1.2	3.6	1.14	1.52	17.0	2.36	1500	485	
	CV014003	14mm ² × 3C	7/1.6	4.4	1.14	1.52	18.5	1.33	1500	699	
	CV022003	22mm ² × 3C	7/2.0	5.5	1.14	2.03	22.0	0.840	1500	1037	
	CV030003	30mm ² × 3C	7/2.3	6.3	1.40	2.03	25.0	0.635	1500	1296	
	CV038003	38mm ² × 3C	7/2.6	7.1	1.40	2.03	27.0	0.497	1000	1633	
	CV050003	50mm ² × 3C	圓形 壓縮	8.2	1.40	2.03	29.0	0.386	1000	1846	
	CV060003	60mm ² × 3C		9.1	1.40	2.03	31.0	0.309	1000	2214	
	CV080003	80mm ² × 3C		10.5	1.40	2.03	34.0	0.234	1000	2836	
	CV100003	100mm ² × 3C		11.9	1.40	2.03	37.0	0.184	800	3518	
	CV125003	125mm ² × 3C		13.2	1.65	2.03	41.0	0.147	800	4349	
	CV150003	150mm ² × 3C		14.7	1.65	2.79	46.0	0.120	800	5300	
	CV200003	200mm ² × 3C		16.6	1.65	2.79	50.0	0.0940	800	6626	
	CV250003	250mm ² × 3C		18.9	1.65	2.79	55.0	0.0736	600	8197	
CV325003	325mm ² × 3C	21.3		2.03	2.79	62.0	0.0576	600	10812		
CNS2655 600V XLPE 電力電纜 (4C)	CV002004	2mm ² × 4C		7/0.6	1.8	0.76	1.14	11.2	9.42	2500	199
	CV003504	3.5mm ² × 4C		7/0.8	2.4	0.76	1.14	12.7	5.30	2000	286
	CV005504	5.5mm ² × 4C		7/1.0	3.0	0.76	1.52	14.9	3.40	2000	390
	CV008004	8mm ² × 4C		7/1.2	3.6	1.14	1.52	18.5	2.36	1500	594
	CV014004	14mm ² × 4C		7/1.6	4.4	1.14	1.52	21.0	1.33	1500	870
	CV022004	22mm ² × 4C		7/2.0	5.5	1.14	2.03	24.0	0.840	1500	1294
	CV030004	30mm ² × 4C		7/2.3	6.3	1.40	2.03	27.0	0.635	1500	1628
	CV038004	38mm ² × 4C	7/2.6	7.1	1.40	2.03	29.0	0.497	1000	2054	
	CV050004	50mm ² × 4C	圓形 壓縮	8.2	1.40	2.03	32.0	0.386	1000	2378	
	CV060004	60mm ² × 4C		9.1	1.40	2.03	34.0	0.309	1000	2862	
	CV080004	80mm ² × 4C		10.5	1.40	2.03	38.0	0.234	1000	3660	
	CV100004	100mm ² × 4C		11.9	1.40	2.03	43.0	0.184	800	4727	
	CV125004	125mm ² × 4C		13.2	1.65	2.03	47.0	0.147	800	5833	
	CV150004	150mm ² × 4C		14.7	1.65	2.79	51.0	0.120	800	6873	
	CV200004	200mm ² × 4C		16.6	1.65	2.79	55.0	0.0940	800	8637	
	CV250004	250mm ² × 4C		18.9	1.65	2.79	60.0	0.0736	600	10682	
CV325004	325mm ² × 4C	21.3		2.03	3.56	70.0	0.0576	600	14383		
CNS2655 15V XLPE 電力電纜 (1C)	15K038	38mm ² × 1C		7/0.6 圓形 壓縮	7.1	4.45	2.03	25.0	0.487	3500	855
	15K050	50mm ² × 1C			8.2	4.45	2.03	26.0	0.378	3500	980
	15K060	60mm ² × 1C			9.1	4.45	2.03	27.0	0.303	3000	1115
	15K080	80mm ² × 1C			10.5	4.45	2.03	28.0	0.229	3000	1330
	15K100	100mm ² × 1C			11.9	4.45	2.03	30.0	0.180	2500	1565
	15K125	125mm ² × 1C			13.2	4.45	2.03	31.0	0.144	2500	1845
	15K150	150mm ² × 1C			14.7	4.45	2.03	34.0	0.118	2000	2175
	15K200	200mm ² × 1C	16.6		4.45	2.03	36.0	0.0922	2000	2630	
	15K250	250mm ² × 1C	18.9		4.45	2.03	38.0	0.0722	1500	3165	
	15K325	325mm ² × 1C	21.3		4.45	2.79	41.0	0.0565	1500	3880	
CNS2655 25V XLPE 電力電纜 (1C)	25K038	38mm ² × 1C	7/0.6 圓形 壓縮	7.1	6.60	2.03	29.5	0.487	3600	1050	
	25K050	50mm ² × 1C		8.2	6.60	2.03	30.0	0.378	3600	1180	
	25K060	60mm ² × 1C		9.1	6.60	2.03	32.0	0.303	3000	1325	
	25K080	80mm ² × 1C		10.5	6.60	2.03	33.0	0.229	3000	1585	
	25K100	100mm ² × 1C		11.9	6.60	2.03	35.0	0.180	2800	1830	
	25K125	125mm ² × 1C		13.2	6.60	2.03	36.0	0.144	2800	2125	
	25K150	150mm ² × 1C		14.7	6.60	2.03	38.0	0.118	2000	2425	
	25K200	200mm ² × 1C		16.6	6.60	2.03	40.0	0.0922	2000	2895	
	25K250	250mm ² × 1C		18.9	6.60	2.03	42.5	0.0722	1800	3440	
	25K325	325mm ² × 1C		21.3	6.60	2.79	47.0	0.0565	1500	4345	