

600V 低煙無毒 (鹵) 電纜

- ★ 2C、3C、4C 產品非常備規格品需另確認庫存或以 MOQ 訂製
- 適用領域及範圍：特殊公共場所，地下室之輸配電，如捷運、機場、醫院等...
- 額定電壓：600V
- 額定溫度：90°C
- 導體：圓形銅絞線
- 絕緣：XLPE 交連 PE
- 被覆：LSFH 低煙無毒



產品類別	產品編號	截面積 × 芯數 mm ² × C	導體		絕緣 厚度 mm	被覆厚度 mm	完成外徑 mm	最大導體 電阻 Ω/km	最小絕緣 電阻 MΩ-km	
			構造 NO./mm	外徑 mm						
低煙無毒 (鹵) 電纜 (1C)	XL0020001	2 mm ² × 1C	7/0.6	1.8	0.76	0.38	4.4	9.24	2500	
	XL0035001	3.5 mm ² × 1C	7/0.8	2.4	0.76	0.38	5.0	5.20	2000	
	XL0055001	5.5 mm ² × 1C	7/1.0	3.0	0.76	0.38	5.6	3.33	2000	
	XL0080001	8 mm ² × 1C	7/1.2	3.6	1.14	0.38	6.6	2.31	1500	
	XL0140001	14 mm ² × 1C	圓形 壓縮	4.4	1.14	0.76	8.7	1.30	1500	
	XL0220001	22 mm ² × 1C		5.5	1.14	0.76	9.8	0.824	1500	
	XL0300001	30 mm ² × 1C		6.3	1.40	0.76	11.1	0.623	1500	
	XL0380001	38 mm ² × 1C		7.1	1.40	0.76	11.9	0.487	1000	
	XL0500001	50 mm ² × 1C		8.2	1.40	1.14	13.7	0.378	1000	
	XL0600001	60 mm ² × 1C		9.1	1.40	1.14	14.6	0.303	1000	
	XL0800001	80 mm ² × 1C		10.5	1.40	1.14	16.0	0.229	1000	
	XL1000001	100 mm ² × 1C		11.9	1.40	1.14	17.4	0.180	800	
	XL1250001	125 mm ² × 1C		13.2	1.65	1.14	19.2	0.144	800	
	XL1500001	150 mm ² × 1C		14.7	1.65	1.65	21.7	0.118	800	
	XL2000001	200 mm ² × 1C		16.6	1.65	1.65	23.6	0.0922	800	
	XL2500001	250 mm ² × 1C		18.9	1.65	1.65	25.9	0.0722	600	
XL3250001	325 mm ² × 1C	21.3		2.03	1.65	29.1	0.0565	600		
低煙無毒 (鹵) 電纜 (2C)	XL0020002	2 mm ² × 2C		7/0.6	1.8	0.76	1.14	9.8	9.42	2500
	XL0035002	3.5 mm ² × 2C		7/0.8	2.4	0.76	1.14	11.0	5.30	2000
	XL0055002	5.5 mm ² × 2C		7/1.0	3.0	0.76	1.14	12.2	3.40	2000
	XL0080002	8 mm ² × 2C	7/1.2	3.6	1.14	1.52	16.0	2.36	1500	
	XL0140002	14 mm ² × 2C	圓形 壓縮	4.4	1.14	1.52	17.2	1.33	1500	
	XL0220002	22 mm ² × 2C		5.5	1.14	1.52	19.5	0.840	1500	
	XL0300002	30 mm ² × 2C		6.3	1.40	2.03	23.1	0.635	1500	
	XL0380002	38 mm ² × 2C		7.1	1.40	2.03	24.7	0.497	1000	
	XL0500002	50 mm ² × 2C		8.2	1.40	2.03	26.9	0.386	1000	
	XL0600002	60 mm ² × 2C		9.1	1.40	2.03	28.7	0.309	1000	
	XL0800002	80 mm ² × 2C		10.5	1.40	2.03	31.5	0.234	1000	
	XL1000002	100 mm ² × 2C		11.9	1.40	2.03	34.3	0.184	800	
	XL1250002	125 mm ² × 2C		13.2	1.65	2.03	37.9	0.147	800	
	XL1500002	150 mm ² × 2C		14.7	1.65	2.03	40.9	0.120	800	
	XL2000002	200 mm ² × 2C		16.6	1.65	2.79	46.4	0.0940	800	
	XL2500002	250 mm ² × 2C		18.9	1.65	2.79	51.0	0.0736	600	
XL3250002	325 mm ² × 2C	21.3		2.03	2.79	57.4	0.0576	600		

產品類別	產品編號	截面積 × 芯數 mm ² × C	導體		絕緣 厚度 mm	被覆厚度 mm	完成外徑 mm	最大導體 電阻 Ω/km	最小絕緣 電阻 MΩ-km	
			構造 NO./mm	外徑 mm						
低煙無毒 (鹵) 電纜 (3C)	XL0020003	2 mm ² × 3C	7/0.6	1.8	0.76	1.14	10.4	9.42	2500	
	XL0035003	3.5 mm ² × 3C	7/0.8	2.4	0.76	1.14	11.6	5.30	2000	
	XL0055003	5.5 mm ² × 3C	7/1.0	3.0	0.76	1.14	12.9	3.40	2000	
	XL0080003	8 mm ² × 3C	7/1.2	3.6	1.14	1.52	17.0	2.36	1500	
	XL0140003	14 mm ² × 3C	圓形 壓縮	4.4	1.14	1.52	18.5	1.33	1500	
	XL0220003	22 mm ² × 3C		5.5	1.14	2.03	22.0	0.840	1500	
	XL0300003	30 mm ² × 3C		6.3	1.40	2.03	25.0	0.635	1500	
	XL0380003	38 mm ² × 3C		7.1	1.40	2.03	27.0	0.497	1000	
	XL0500003	50 mm ² × 3C		8.2	1.40	2.03	29.0	0.386	1000	
	XL0600003	60 mm ² × 3C		9.1	1.40	2.03	31.0	0.309	1000	
	XL0800003	80 mm ² × 3C		10.5	1.40	2.03	34.0	0.234	1000	
	XL1000003	100 mm ² × 3C		11.9	1.40	2.03	37.0	0.184	800	
	XL1250003	125 mm ² × 3C		13.2	1.65	2.03	41.0	0.147	800	
	XL1500003	150 mm ² × 3C		14.7	1.65	2.79	46.0	0.120	800	
	XL2000003	200 mm ² × 3C		16.6	1.65	2.79	50.0	0.0940	800	
	XL2500003	250 mm ² × 3C		18.9	1.65	2.79	55.0	0.0736	600	
XL3250003	325 mm ² × 3C	21.3		2.03	2.79	62.0	0.0576	600		
低煙無毒 (鹵) 電纜 (4C)	XL0020004	2 mm ² × 4C		7/0.6	1.8	0.76	1.14	11.2	9.42	2500
	XL0035004	3.5 mm ² × 4C		7/0.8	2.4	0.76	1.14	12.7	5.30	2000
	XL0055004	5.5 mm ² × 4C		7/1.0	3.0	0.76	1.52	14.9	3.40	2000
	XL0080004	8 mm ² × 4C	7/1.2	3.6	1.14	1.52	18.5	2.36	1500	
	XL0140004	14 mm ² × 4C	圓形 壓縮	4.4	1.14	1.52	21.0	1.33	1500	
	XL0220004	22 mm ² × 4C		5.5	1.14	2.03	24.0	0.840	1500	
	XL0300004	30 mm ² × 4C		6.3	1.40	2.03	27.0	0.635	1500	
	XL0380004	38 mm ² × 4C		7.1	1.40	2.03	29.0	0.497	1000	
	XL0500004	50 mm ² × 4C		8.2	1.40	2.03	32.0	0.386	1000	
	XL0600004	60 mm ² × 4C		9.1	1.40	2.03	34.0	0.309	1000	
	XL0800004	80 mm ² × 4C		10.5	1.40	2.03	38.0	0.234	1000	
	XL1000004	100 mm ² × 4C		11.9	1.40	2.03	43.0	0.184	800	
	XL1250004	125 mm ² × 4C		13.2	1.65	2.03	47.0	0.147	800	
	XL1500004	150 mm ² × 4C		14.7	1.65	2.79	51.0	0.120	800	
	XL2000004	200 mm ² × 4C		16.6	1.65	2.79	55.0	0.0940	800	
	XL2500004	250 mm ² × 4C		18.9	1.65	2.79	60.0	0.0736	600	
XL3250004	325 mm ² × 4C	21.3		2.03	3.56	70.0	0.0576	600		