

超軟電纜 / 耐曲尺防油電纜 ★部分規格非常規品須另洽詢，另可訂製隔離遮蔽型

- 適用領域及範圍：馬達配線、自動化設備、室內外裝潢配線等佈線狹窄之工作場合。
- 額定電壓：600V
- 額定溫度：60/80/105°C
- 導體：裸軟銅線 B.C
- 絕緣 / 被覆：超軟 PVC 聚氯乙烯
- 特性：具優異柔軟度，增加工作的方便性



產品類別	產品編號	截面積 × 芯數 mm ² × C	導體		絕緣		被覆厚度 mm	完成外徑 mm	最大導體電阻 Ω/km	最小絕緣電阻 MΩ-km
			構造 NO./mm	外徑 mm	厚度 mm	外徑 mm				
超軟電纜 (0.3 mm ²)	IN03502	0.3 mm ² × 2C	12/0.18	0.72	0.39	1.50	0.6	4.5	61.9	50
	IN03503	0.3 mm ² × 3C	12/0.18	0.72	0.39	1.50	0.6	4.8	61.9	50
	IN03504	0.3 mm ² × 4C	12/0.18	0.72	0.39	1.50	0.6	5.0	61.9	50
	IN03505	0.3 mm ² × 5C	12/0.18	0.72	0.39	1.50	0.6	5.8	61.9	50
	IN03506	0.3 mm ² × 6C	12/0.18	0.72	0.39	1.50	0.6	6.5	61.9	50
	IN03507	0.3 mm ² × 7C	12/0.18	0.72	0.39	1.50	0.6	6.5	61.9	50
	IN03508	0.3 mm ² × 8C	12/0.18	0.72	0.39	1.50	0.7	7.0	61.9	50
	IN03510	0.3 mm ² × 10C	12/0.18	0.72	0.39	1.50	0.8	8.0	61.9	50
	IN03512	0.3 mm ² × 12C	12/0.18	0.72	0.39	1.50	0.8	8.5	61.9	50
	IN03516	0.3 mm ² × 16C	12/0.18	0.72	0.39	1.50	0.9	9.5	61.9	50
	IN03520	0.3 mm ² × 20C	12/0.18	0.72	0.39	1.50	1.0	10.5	61.9	50
	IN03524	0.3 mm ² × 24C	12/0.18	0.72	0.39	1.50	1.0	11.8	61.9	50
	IN03530	0.3 mm ² × 30C	12/0.18	0.72	0.39	1.50	1.0	12.5	61.9	50
	IN03536	0.3 mm ² × 36C	12/0.18	0.72	0.39	1.50	1.0	13.5	61.9	50
	IN03540	0.3 mm ² × 40C	12/0.18	0.72	0.39	1.50	1.1	14.5	61.9	50
	IN03550	0.3 mm ² × 50C	12/0.18	0.72	0.39	1.50	1.1	15.5	61.9	50
超軟電纜 (0.5 mm ²)	IN05002	0.5 mm ² × 2C	20/0.18	0.95	0.43	1.80	0.8	5.0	36.7	50
	IN05003	0.5 mm ² × 3C	20/0.18	0.95	0.43	1.80	0.8	5.3	36.7	50
	IN05004	0.5 mm ² × 4C	20/0.18	0.95	0.43	1.80	0.8	6.0	36.7	50
	IN05005	0.5 mm ² × 5C	20/0.18	0.95	0.43	1.80	0.8	6.8	36.7	50
	IN05006	0.5 mm ² × 6C	20/0.18	0.95	0.43	1.80	0.8	7.5	36.7	50
	IN05007	0.5 mm ² × 7C	20/0.18	0.95	0.43	1.80	0.8	7.5	36.7	50
	IN05008	0.5 mm ² × 8C	20/0.18	0.95	0.43	1.80	1.0	8.0	36.7	50
	IN05010	0.5 mm ² × 10C	20/0.18	0.95	0.43	1.80	1.0	9.5	36.7	50
	IN05012	0.5 mm ² × 12C	20/0.18	0.95	0.43	1.80	1.0	10.0	36.7	50
	IN05016	0.5 mm ² × 16C	20/0.18	0.95	0.43	1.80	1.1	11.0	36.7	50
	IN05020	0.5 mm ² × 20C	20/0.18	0.95	0.43	1.80	1.3	12.5	36.7	50
	IN05024	0.5 mm ² × 24C	20/0.18	0.95	0.43	1.80	1.3	13.3	36.7	50
	IN05030	0.5 mm ² × 30C	20/0.18	0.95	0.43	1.80	1.4	15.0	36.7	50
	IN05036	0.5 mm ² × 36C	20/0.18	0.95	0.43	1.80	1.4	15.8	36.7	50
	IN05040	0.5 mm ² × 40C	20/0.18	0.95	0.43	1.80	1.5	16.2	36.7	50
	IN05050	0.5 mm ² × 50C	20/0.18	0.95	0.43	1.80	1.5	18.2	36.7	50
超軟電纜 (0.75 mm ²)	IN07502	0.75 mm ² × 2C	30/0.18	1.15	0.58	2.30	1.0	6.5	24.4	50
	IN07503	0.75 mm ² × 3C	30/0.18	1.15	0.58	2.30	1.0	7.0	24.4	50
	IN07504	0.75 mm ² × 4C	30/0.18	1.15	0.58	2.30	1.0	7.5	24.4	50
	IN07505	0.75 mm ² × 5C	30/0.18	1.15	0.58	2.30	1.0	8.5	24.4	50
	IN07506	0.75 mm ² × 6C	30/0.18	1.15	0.58	2.30	1.1	9.5	24.4	50
	IN07507	0.75 mm ² × 7C	30/0.18	1.15	0.58	2.30	1.1	9.5	24.4	50
	IN07508	0.75 mm ² × 8C	30/0.18	1.15	0.58	2.30	1.2	10.1	24.4	50
	IN07510	0.75 mm ² × 10C	30/0.18	1.15	0.58	2.30	1.2	11.0	24.4	50
IN07512	0.75 mm ² × 12C	30/0.18	1.15	0.58	2.30	1.2	11.8	24.4	50	
IN07516	0.75 mm ² × 16C	30/0.18	1.15	0.58	2.30	1.4	13.5	24.4	50	

產品類別	產品編號	截面積 × 芯數 mm ² × C	導體		絕緣		被覆厚度 mm	完成外徑 mm	最大導體電阻 Ω/km	最小絕緣電阻 MΩ-km	
			構造 NO./mm	外徑 mm	厚度 mm	外徑 mm					
超軟電纜 (0.75 mm ²)	IN07520	0.75 mm ² × 20C	30/0.18	1.15	0.58	2.30	1.4	15.3	24.4	50	
	IN07524	0.75 mm ² × 24C	30/0.18	1.15	0.58	2.30	1.5	16.9	24.4	50	
	IN07530	0.75 mm ² × 30C	30/0.18	1.15	0.58	2.30	1.5	17.8	24.4	50	
	IN07536	0.75 mm ² × 36C	30/0.18	1.15	0.58	2.30	1.5	19.4	24.4	50	
	IN07540	0.75 mm ² × 40C	30/0.18	1.15	0.58	2.30	1.6	20.1	24.4	50	
	IN07550	0.75 mm ² × 50C	30/0.18	1.15	0.58	2.30	1.8	23.5	24.4	50	
	超軟電纜 (1.25 mm ²)	IN12502	1.25 mm ² × 2C	50/0.18	1.50	0.51	2.50	1.0	6.8	15.1	50
		IN12503	1.25 mm ² × 3C	50/0.18	1.50	0.51	2.50	1.1	7.5	15.1	50
		IN12504	1.25 mm ² × 4C	50/0.18	1.50	0.51	2.50	1.2	7.8	15.1	50
		IN12505	1.25 mm ² × 5C	50/0.18	1.50	0.51	2.50	1.2	8.8	15.1	50
IN12506		1.25 mm ² × 6C	50/0.18	1.50	0.51	2.50	1.3	10.0	15.1	50	
IN12507		1.25 mm ² × 7C	50/0.18	1.50	0.51	2.50	1.3	10.0	15.1	50	
IN12508		1.25 mm ² × 8C	50/0.18	1.50	0.51	2.50	1.3	11.0	15.1	50	
IN12510		1.25 mm ² × 10C	50/0.18	1.50	0.51	2.50	1.3	13.0	15.1	50	
IN12512		1.25 mm ² × 12C	50/0.18	1.50	0.51	2.50	1.3	13.2	15.1	50	
IN12516		1.25 mm ² × 16C	50/0.18	1.50	0.51	2.50	1.3	14.8	15.1	50	
IN12520		1.25 mm ² × 20C	50/0.18	1.50	0.51	2.50	1.3	16.3	15.1	50	
IN12524		1.25 mm ² × 24C	50/0.18	1.50	0.51	2.50	1.5	18.0	15.1	50	
IN12530		1.25 mm ² × 30C	50/0.18	1.50	0.51	2.50	1.5	19.0	15.1	50	
IN12536		1.25 mm ² × 36C	50/0.18	1.50	0.51	2.50	1.6	20.8	15.1	50	
IN12540		1.25 mm ² × 40C	50/0.18	1.50	0.51	2.50	1.6	21.9	15.1	50	
IN12550		1.25 mm ² × 50C	50/0.18	1.50	0.51	2.50	1.8	24.5	15.1	50	
超軟電纜 (2 mm ²)	IN20002	2 mm ² × 2C	37/0.26	1.80	0.60	3.00	1.2	8.0	9.79	50	
	IN20003	2 mm ² × 3C	37/0.26	1.80	0.60	3.00	1.3	8.5	9.79	50	
	IN20004	2 mm ² × 4C	37/0.26	1.80	0.60	3.00	1.3	9.5	9.79	50	
	IN20005	2 mm ² × 5C	37/0.26	1.80	0.60	3.00	1.3	10.6	9.79	50	
	IN20006	2 mm ² × 6C	37/0.26	1.80	0.60	3.00	1.4	12.0	9.79	50	
	IN20007	2 mm ² × 7C	37/0.26	1.80	0.60	3.00	1.5	12.0	9.79	50	
	IN20008	2 mm ² × 8C	37/0.26	1.80	0.60	3.00	1.5	13.0	9.79	50	
	IN20010	2 mm ² × 10C	37/0.26	1.80	0.60	3.00	1.5	15.1	9.79	50	
	IN20012	2 mm ² × 12C	37/0.26	1.80	0.60	3.00	1.5	15.5	9.79	50	
	IN20016	2 mm ² × 16C	37/0.26	1.80	0.60	3.00	1.5	17.1	9.79	50	
	IN20020	2 mm ² × 20C	37/0.26	1.80	0.60	3.00	1.6	18.6	9.79	50	
	IN20024	2 mm ² × 24C	37/0.26	1.80	0.60	3.00	1.8	21.4	9.79	50	
	IN20030	2 mm ² × 30C	37/0.26	1.80	0.60	3.00	1.8	23.0	9.79	50	
	IN20036	2 mm ² × 36C	37/0.26	1.80	0.60	3.00	1.9	24.8	9.79	50	
	超軟電纜 (3.5 mm ²)	IN35002	3.5 mm ² × 2C	65/0.26	2.40	0.82	4.00	1.2	10.5	5.42	50
		IN35003	3.5 mm ² × 3C	65/0.26	2.40	0.82	4.00	1.2	10.8	5.42	50
IN35004		3.5 mm ² × 4C	65/0.26	2.40	0.82	4.00	1.4	12.5	5.42	50	
IN35005		3.5 mm ² × 5C	65/0.26	2.40	0.82	4.00	1.5	14.0	5.42	50	
IN35006		3.5 mm ² × 6C	65/0.26	2.40	0.82	4.00	1.5	15.0	5.42	50	
IN35007		3.5 mm ² × 7C	65/0.26	2.40	0.82	4.00	1.5	15.0	5.42	50	
超軟電纜 (5.5 mm ²)		IN55002	5.5 mm ² × 2C	104/0.26	3.00	1.00	5.00	1.5	12.0	6.10	50
	IN55003	5.5 mm ² × 3C	104/0.26	3.00	1.00	5.00	1.5	14.2	6.10	50	
	IN55004	5.5 mm ² × 4C	104/0.26	3.00	1.00	5.00	1.5	15.6	6.10	50	
	IN55005	5.5 mm ² × 5C	104/0.26	3.00	1.00	5.00	1.5	16.5	6.10	50	
	IN55006	5.5 mm ² × 6C	104/0.26	3.00	1.00	5.00	1.6	18.2	6.10	50	
超軟電纜 (8 mm ²)	IN80002	8 mm ² × 2C	148/0.26	3.70	1.20	6.00	1.4	14.0	2.54	50	
	IN80003	8 mm ² × 3C	148/0.26	3.70	1.20	6.00	1.5	16.5	2.54	50	
	IN80004	8 mm ² × 4C	148/0.26	3.70	1.20	6.00	1.5	18.0	2.54	50	
	超軟電纜 (14 mm ²)	IN140002	14 mm ² × 2C	259/0.26	4.90	1.20	7.30	1.7	17.5	1.43	30
IN140003		14 mm ² × 3C	259/0.26	4.90	1.20	7.30	1.8	20.0	1.43	30	
IN140004		14 mm ² × 4C	259/0.26	4.90	1.20	7.30	1.8	22.0	1.43	30	
超軟電纜 (22 mm ²)	IN220004	22 mm ² × 4C	420/0.26	6.80	1.30	9.50	1.8	27.0	0.89	30	